

Part number

CHIN 10



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "57.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size "57.27"

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	86,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV-GL, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163088
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Packaging length	305,00 mm
Packaging height	180,00 mm
Packaging width	275,00 mm
Packaging weight	3,44 kg
Packaging volume	15,10 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747187589
Sub-packaging weight	0,43 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187596

Part number CHIN 10



Catalogue drawings

Catalogue drawings

CH.N - MA, MF.N custodie grandezza "57.27" versione LS-TYPE

frutti inseribili:	pag.
CDD 42 poli + @	61 *
CDE 15 poli + @	81 *
CSH 10 poli + @	89 *
CCE 10 poli + @	90 *
CNE, CSE, JONE, JCSE 10 poli + @	97 e 107 *
CSS 10 poli + @	119 *
CTE, CTSE **)	127 *
CMSE 3+2 (aux) poli + @	135 *
CMCE 3+2 (aux) poli + @	134 *
CX 8/24 poli + @	151 *
MIXO 3 moduli	160-195 *

interassi fissaggio frutti: 57 x 27 mm

* riferimenti di pagina catalogo CN.12

descrizione	codice articolo	uscita M
custodia da incasso, con 2 leve	CHIN 10	
custodia da parete, alta, con 2 leve	MAPN 10.32	32
con pinoli, uscita orizzontale		
con pinoli, uscita orizzontale, alta	MHON 10.25	25
con pinoli, uscita verticale	MFON 10.32	32
con pinoli, uscita verticale, alta	MHVN 10.25	25
con pinoli, uscita verticale, alta	MFVN 10.32	32

dimensioni in mm

CHIN 10

MAPN 10.32

MHON 10.25

MFON 10.32

MHVN 10.25

MFVN 10.32

*) solo nella custodia CHIN 10

dim. di fissaggio custodia da incasso in mm

ventilatura a forno con polvere epossipoliesterica nera RAL 9005
 leva di chiusura in materiale termoplastico auto-estinguente, di colore nero RAL 9005 (leva di ricambio pag. 12)

le misure indicate non sono impegnative e possono essere variate senza alcun preavviso

6

CH.N - MA, MF.N enclosures size "57.27" LS-TYPE version

inserts:	page
CDD 42 poles + @	61 *
CDE 15 poles + @	81 *
CSH 10 poles + @	89 *
CCE 10 poles + @	90 *
CNE, CSE, JONE, JCSE 10 poles + @	97 and 107 *
CSS 10 poles + @	119 *
CTE, CTSE **)	127 *
CMSE 3+2 (aux) poles + @	135 *
CMCE 3+2 (aux) poles + @	134 *
CX 8/24 poles + @	151 *
MIXO 3 modules	160-195 *

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

description	part no.	entry M
bulkhead mounting housing, with 2 levers	CHIN 10	
surface mounting housing, high construction, with 2 levers	MAPN 10.32	32
with pegs, side entry		
with pegs, side entry, high construction	MHON 10.25	25
with pegs, top entry	MFON 10.32	32
with pegs, top entry, high construction	MHVN 10.25	25
with pegs, top entry, high construction	MFVN 10.32	32

dimensioni in mm

CHIN 10

MAPN 10.32

MHON 10.25

MFON 10.32

MHVN 10.25

MFVN 10.32

**) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

kin powder coating with RAL 9005 black epoxy polyester powder
 -RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

6

Notes

Dimensions shown in mm are not binding and may be changed without notice.