

Part number

# CX 01 YAF



Female modular insert, Mixo series, screw terminal connections - 90° angled for cable lug, 1 pole, 2 modules, 200 A 1000 V 8 kV 3


Product description		Material properties	
<b>Product type</b>	Modular insert	<b>Main material</b>	Polycarbonate
<b>Series</b>	Mixo	<b>Other materials</b>	Contacts: copper alloy
<b>Connection type</b>	Screw terminal connection	<b>Colour</b>	RAL 7032 grey
<b>Gender</b>	Female		Compliant with exemption
<b>N. of poles</b>	1 pole	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Size</b>	2 modules	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	Angled	<b>REACH SVHC substances</b>	Yes Lead
Technical data		General ordering information	
<b>Current</b>	200 A	<b>EAN13 code</b>	8015747284431
<b>Voltage</b>	1000 V	<b>eCl@ss 8.1</b>	27440205
<b>Rated impulse withstand voltage</b>	8 kV	<b>ETIM 7.0</b>	EC000438
<b>Pollution degree</b>	3	Packaging Information	
<b>Rated voltage according to UL/CSA</b>	600 V	<b>Packaging length</b>	225,00 mm
<b>Contact type</b>	Turned silver plated	<b>Packaging height</b>	130,00 mm
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	<b>Packaging width</b>	150,00 mm
Further technical details		<b>Packaging weight</b>	1,10 kg
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Packaging volume</b>	4,39 dm <sup>3</sup>
<b>Contact resistance</b>	≤ 3 mΩ	<b>Packaging description</b>	Carton box
<b>Weight</b>	84,00 g	<b>Packaging quantity</b>	10 Pcs
<b>Operating temperature range (min, max)</b>	-40 °C ... +125 °C	<b>Packaging EAN code</b>	8015747284448
<b>UL 94 flammability rating</b>	V-0	<b>Sub-packaging weight</b>	0,11 kg
		<b>Sub-packaging description</b>	Plastic bag
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747284455

Part number

# CX 01 YAF



## Catalogue drawings



## Notes

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support

---

Dimensions shown in mm are not binding and may be changed without notice.

---