



## Inductive Sensors Series 30 - NAMUR EN 60947-5-6

Housing M 18 x 1

- Housing material: Brass
- For use in areas with the risk of gas explosion, zone 0
- Sensing distance  $S_n = 5\text{ mm}$

DMT 03 ATEX E 048

IECEX BVS 07.0031



Ex II 1G Ex ia IIC T1-T6 Ga

Ex ia IIC T1-T6 Ga



<b>Technical data</b>	Flush mountable
Operating distance $S_n$	5 mm
Electrical version	2-wire DC
Output	NAMUR EN 60947-5-6
<b>Type</b>	<b>IAS-30-M13-N</b>
<b>Art.-No.</b>	<b>IA 0158</b>
Operating voltage ( $U_B$ )	$U_i = 15\text{ V DC}$
Output current active surface free	> typ. 2 mA
Output current active surface covered	< typ. 1.5 mA
Self-inductance (L)	2 mH
Self-capacitance (C)	250 nF
Permitted residual ripple max.	5 %
Frequency of operating cycles max.	1.5 kHz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Degree of protection IEC 60529	IP 67
Connection cable	10 m, PUR, 2 x 0.34 mm <sup>2</sup>
Housing material	Brass
Active surface	PA / PPO
Lid	PA / PPO
<b>Accessories</b> (delivered with the sensor)	2 nuts M 18 x 1

All specifications are subject to change without notice. (07.06.2019)



**Made in Germany**