



Capacitive Sensors Series 80 - PNP

Housing Ø 26 mm



- Housing material: Stainless steel VA No. 1.4404
- Sensing distance 0,5...20 mm adjustable
- With flange connector M 12 x 1



Technical data	Non-flush mountable
Operating distance Sn	12 mm
Operating distance min./max. adjustable	0.5...20 mm
Electrical version	4-pin DC
Output	Antivalent (NO+NC)
Type PNP	KAS-80-23/170-A-PEEK/VA-Y5
Art.-No.	KA 0693
Connection diagram No.	see below
Operating voltage (U_B)	10...35 V DC
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Output current max. (I_e)	2 x 0...250 mA
Frequency of operating cycles max.	100 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1
Housing material	VA No. 1.4404
Active surface	PEEK (FDA 21 CFR 177.2415)
Lid	PEEK (FDA 21 CFR 177.2415) / VA No. 1.4404

All specifications are subject to change without notice. (02.02.2016)

* With sealed potentiometer screw



Made in Germany