

Part number

MFVN 16.32



Hood, LS-TYPE series, with 4 pegs, M32 top cable entry without adapter, size "77.27", high construction

Product description

| | |
|----------------------|--|
| Product type | Hood |
| Series | LS-TYPE |
| Closing type | With 4 pegs |
| Size | Size "77.27" |
| Cable entry | Top cable entry without adapter M32 |
| Specification | High construction |

Technical data

| | |
|--------------------------------|------|
| IP degree of protection | IP65 |
|--------------------------------|------|

Further technical details

| | |
|---|----------------|
| Weight | 257,00 g |
| Operating temperature range (min, max) | -40°C...+125°C |

Material properties

| | |
|------------------------------|----------------|
| Colour | RAL 9005 black |
| RoHs conformity | Compliant |
| China RoHs - EFUP | E |
| REACH SVHC substances | No |

Approvals / Standards

| | |
|-----------------------|------------|
| Certifications | DNV-GL, BV |
| UL | ECBT2 |
| cUL | ECBT8 |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747163590 |
| eCl@ss 8.1 | 27440202 |
| ETIM 7.0 | EC000437 |


Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging weight | 5,49 kg |
| Packaging volume | 10,68 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 20 Pcs |
| Packaging EAN code | 8015747187800 |
| Sub-packaging weight | 1,37 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747187817 |

Part number MFVN 16.32



Catalogue drawings



Catalogue drawings

| CH..N - MA, MF..N enclosures | | size "77.27" | | LS-TYPE version | |
|--|------------|--|------------|---|--|
| <p>inserts: page</p> <p>CD 40 poles + @ 49+52 *</p> <p>CT, CTS **) 40 poles + @ 56 *</p> <p>CDD 72 poles + @ 62+65 *</p> <p>CDE 32 poles + @ 82+84 *</p> <p>CSH 16 poles + @ 90+92 *</p> <p>CCE 16 poles + @ 98+102 *</p> <p>CNE, CSE, JCNE, JCSE 16 poles + @ 99 and 108 *</p> <p>CSS 16 poles + @ 120+122 *</p> <p>CTE, CTSE **) 16 poles + @ 128 *</p> <p>CMSE 6+2 (aux) poles + @ 137 *</p> <p>CMCE 6+2 (aux) poles + @ 136 *</p> <p>CP 6 poles + @ 149+150 *</p> <p>CX 6/36 e 12/2 poles + @ 152+153 *</p> <p>CX 4/0 e 4/2 poles + @ 154 *</p> <p>MIXO 4 modules 160+195 *</p> <p>insert centre distance: 77,5 x 27 mm</p> <p>* refer to catalogue page CN.12</p> | | <p> housings with double lever</p> | | <p> hoods with 4 pegs</p> | |
| description | part no. | entry M | part no. | entry M | |
| bulkhead mounting housing, with 2 levers | CHIN 16 | | | | |
| surface mounting housing, high construction, with 2 levers | MAPN 16.32 | 32 | | | |
| with pegs, side entry | | | MHON 16.32 | 32 | |
| with pegs, side entry, high construction | | | MFON 16.32 | 32 | |
| with pegs, top entry | | | MHVN 16.32 | 32 | |
| with pegs, top entry, high construction | | | MFVN 16.32 | 32 | |
| <p>**) only in the CHIN 16 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> | | <p>dimensions in mm</p> <p>CHIN 16</p> <p>MAPN 16.32</p> | | <p>dimensions in mm</p> <p>MFON 16.32</p> <p>MFVN 16.32</p> <p>MHON 16.32</p> <p>MHVN 16.32</p> | |
| <p>dimensions shown are not binding and may be changed without notice</p> | | | | | |