


M8, female, angled, 3 poles, sensor-/actuator cable, high-temperature









| Product data | | | |
|---|----------------------------|--|--|
| Item description | HT-SWKP3-10/S2430 | | |
| Item-No. | 8039485 | | |
| Length | 10m | | |
| Customs tariff-No. | 85444290 | | |
| Step-File | HT-SWKP3_S2430.stp | | |
| EAN | 4047106001605 | | |
| Technical data | | | |
| Connector | female, angled, M8 | | |
| Number of pins | 3 | | |
| Pin assignment | 1 BN, 3 BU, 4 BK | | |
| Rated voltage | 60V | | |
| Current load per pin (at 40°C) | 4A | | |
| Insulation resistance | ≥10°Ω | | |
| Ambient temperature product | -20°C+150°C | | |
| Contact material | Metal, CuZn, gold-plated | | |
| Contact-carrier material | Plastic, PBT GF, BK | | |
| Grip body material | Plastic, PBT GF, BK | | |
| Coupling nut material | Metal, CuZn, nickel-plated | | |
| Sealing (female) material | FPM/FKM | | |
| Standards | IEC 61076-2-104 | | |
| Degree of protection (mounted) | IP65 | | |
| Mechanical life-cycle | >100 mating cycles | | |
| | 50mm stripped | | |
| Cable end assembly | John Stripped | | |
| Cable end assembly Degree of pollution | 3 | | |



Cable PTFE, S2430, high temp

The thermal resistance of this high-temperature cable extends from -190°C to +260°C. Due to its fully fluorinated jacket and wire insulation, the cable is perfectly suited for applications in high-frequency cables, as control cable in critical temperature areas, and in the computer-, and aviation industry. In addition, it stands out through a very good chemical strength, as well as its ozone- and weather resistance.

| Outer diameter of jacket | 3.80 mm |
|---------------------------|---|
| Cable-jacket material | PTFE |
| Jacket color | WH, similar RAL9003 |
| Wire cross-section | 5 x AWG22 |
| Wire insulation material | PTFE |
| Wire colors | BN, WH, BU, BK, GY |
| Wire structure | 7 x 0.254 mm |
| Bending radius (fixed) | 5 x Ø-cable |
| Bending radius (repeated) | 10 x Ø-cable |
| Temperature range (fixed) | -190°C+260°C |
| Rated voltage cable | ≤250 V |
| Special features | seawater resistant, LABS free, RoHs compliant, ozone resistant, UV resistant, hydrolysis proof, flexibility at low temperature, non-flammable, low emission of smoke, excellent chemicals resistance, flexible at high temperatures |
| Classification | |

| Classification | | |
|----------------|----------|--|
| eCl@ss 6.0 | 27279218 | |
| eCl@ss 7.0 | 27279218 | |
| eCl@ss 8.0 | 27279218 | |
| eCl@ss 9.0 | 27060311 | |
| ETIM 5.0 | EC001855 | |
| ETIM 6.0 | EC001855 | |

| Α | cc | es | SO | rı | es |
|---|----|----|----|----|----|

Mounting-set, M8 https://www.escha.net/en/products/standard/accessories-for-connectivity/8047663

Torque-wrench set

escha.net/en/products/standard/accessories-for-connectivity/8055431

 $\label{lem:marking_marking} Marking\ rings\ \varnothing\ 9mm \\ \text{https://www.escha.net/en/products/standard/accessories-for-connectivity/?p=1&o=3&n=15&f=809} \\$

Cable Stripping Tool https://www.escha.net/en/products/standard/accessories-for-connectivity/8066216

Cable Stripping Tool roducts/standard/accessories-for-connectivity/8066215

Link to product

https://www.escha.net/en/products/standard/sensoractuator-connectors/8039485