



Capacitive Sensors Series 80 - PNP - StEx - ATEX

Housing M 12 x 1

- For use in areas with the risk of dust explosion, zone 20
- For use in areas with the risk of gas explosion, zone 1
- Housing material: Stainless steel VA No. 1.4305 / AISI 303
- Sensing distance 0...6 mm adjustable

DMT 01 ATEX E 157

IECEX BVS 07.0015

Ex G Ex mb IIC T4 Gb

Ex mb IIC T4 Gb



Ex D Ex ta/tb IIIC T101°C Da/Db

Ex ta/tb IIIC T101°C Da/Db



Technical data	Flush mountable
Operating distance S_n	2 mm
Operating distance min. / max. adjustable	0...6 mm
Electrical version	4-wire DC
Output function	Antivalent
Type PNP current	KAS-80-A12-A-M12-PTFE/VAb-Z03-1-2G-1/2D
Type PNP	KAS-80-A12-A-StEx
Art.-No.	KA 1564
Operating voltage (U_B)	10...30 V DC
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
Operating current (I_a)	2 x 0...150 mA
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-20...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection cable	3 m, PVC, 5 x 0.14 mm ²
Housing material	Stainless steel VA No. 1.4305 / AISI 303
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PC (FDA 21 CFR 177.1580)
Media optimized	Yes
Accessories (delivered with the sensor)	2 nuts M 12 x 1

All specifications are subject to change without notice. (22.03.2021)



* With sealed potentiometer screw

Made in Germany