



Ex position switch

ExM 14 DL 1Ö/1S - 2m

Material number: 1189209 (Material number old: 14123304)

Features/Options:


- Ex zone 1 and 21
- Thermoplastic enclosure
- Double insulated 
- Mounting details to EN 50047
- Suitable for in-line mounting
- With pre-wired cable
- Actuator: Long rocking lever DL
- Actuating speed max. 0.5 m/s with a vertical actuating angle of 45°

Notes

- With metal roller available on request

- Wear-resistant plastic roller
- Lever can be repositioned in 10° steps clockwise or counter-clockwise
- Actuator can be repositioned by 180°
- Attention: Please state required international approvals with your order!

Dimensions



Technical data

Applied standards	EN 60947-5-1, EN 60079-0, EN 60079-1, EN 60079-31
Enclosure	thermoplastic, glass-fibre reinforced, impact resistant, self-extinguishing UL 94 V-0
Degree of protection	IP 65 to IEC/EN 60529
Contact material	silver
Switching system	snap action
Switching elements	1 NC/1 NO contact, type Za
Connection	pre-wired cable H05VV-F
Cable cross-section	4 x 0.75 mm ² (incl. conductor ferrules)
Cable length	2 m
Rated impulse withstand voltage U_{imp}	4 kV
Rated insulation voltage U_i	250 V
Conventional thermal current I_{the}	5 A
Rated operating current/voltage I_e/U_e	5 A/250 VAC; 0.2 A/230 VDC
Utilisation category	AC-1; DC-1
Short-circuit protection	5 A gG/gN fuse
Ambient temperature	-20 °C ... +60 °C
Mechanical life	> 1 million operations
Operation cycles	max. 1800/h

Errors and omissions excepted.



Ex position switch

ExM 14 DL 1Ö/1S - 2m

Material number: 1189209 (Material number old: 14123304)

Technical data

Repeat accuracy of switching points ± 0.1 mm


Contact opening max. 2 x 4 mm

Ex marking
 II 2G Ex db IIC T6 Gb,
 II 2D Ex tb IIIC T80 °C Db
IECEX Ex d IIC T6 Gb
Ex tb IIIC T80 °C Db

Approvals
PTB 00 ATEX 1006 X
IECEX PTB 13.0019X



Contact diagram



Switching diagram

